
# aokin ReferenceMatrixMaterial

### ΟΤΑ

Order No.: RMM-04-1553-2r

for analysis of Ochratoxin A (OTA) in Animal feed



Ochratoxin A (OTA)

#### Specification

Lot No.	004155302080615275
Matrix Type	Animal feed
Analyte	Ochratoxin A (OTA)
Weight/Volume	50 g
Storage	-18 °C
Retest	02/2026

	Concentration $x_{PT}$ [µg/kg]	data points n	satisfactory range $x_{PT} ~\pm 2 ~\sigma_{PT} ~[\mu { m g/kg}]$	uncertainty* $2 u(x_{PT})[\mu g/kg]$
Ochratoxin A	17,10	9	7,00 - 27,20	2,08

\*Expanded uncertainty with k=2 for approximately 95% level of confidence (PA/PH/OMCL(18)153R1 CORR Evaluation of Measurement Uncertainty - Annex 2.5).

aokin AG · Robert-Rössle-Str. 10 · 13125 Berlin · Germany Tel. +49 30 94 89 21 60 · Fax +49 30 94 89 21 61 · info@aokin.com· www.aokin.com

# aokin ReferenceMatrixMaterial

#### Comments

*aokin* reference matrix material is naturally contaminated and homogenized. Concentration of the analyte is determinate in a proficiency round. Unweighted mean value of the means of accepted sets of data, each set being obtained in a different laboratory and/or with a different method of determination such as HPLC/MS/MS, HPLC/FLD.

The certified value and its uncertainty are traceable to the International System of Units (SI) as chemical mass fraction as  $\mu g/kg$ . The assigned value, the satisfactory range and the expanded uncertainty are given. The minimum amount of sample to be used is 10 g.

### Calculation of the assigned value $x_{PT}$

The Assigned Value is the value attributed to a particular property of interlaboratory proficiency test (definition from ISO13528:2016).  $x_{PT}$  is derived from participants quantitative results obtained with confirmatory analysis. The procedure for determining is from the Algorithm A (ISO 13528:2016) or from the median.

The standard uncertainty is expanded by a factor f = 1,25 and is calculated as:  $u(x_{PT}) = f \frac{\sigma_{PT}}{\sqrt{n}}$  (uncertainty of the characterization) where:

- $\sigma_{PT}$  is the robust estimate of the participant standard deviation;
- $\sigma_{PT} = b \cdot x_{PT}$  where b is the relative robust estimate of the participant standard deviation
- n is the number of participants used in calculating the robust assigned values.

The satisfactory range is calculated from the expanded (k=2) standard deviation of the proficiency assessment: The satisfactory range equals  $x_{PT} \pm 2 \sigma_{PT}$ .